

TANE Sirens and Speakers are available as "SPECIAL ORDER" items only in surface mount, flush mount and speaker or siren horn configurations.

Please call or email for special-order lead times, minimum order quantities and delivery information.

### TANE SCS 101 • Self Contained Dual Tone Indoor Siren



**Specifications:**

- **Housing Material:** ABS Plastic
- **Speaker Type:** Voice coil impedance-8 ohm
- **Rated Input Voltage:** 12 VDC
- **Range Voltage:** 6-15VDC
- **Sound Level:** 110db/m
- **Current Draw:** 400mA @12VDC 8 ohm load
- **Tone Frequency:** Steady-1200HZ  
Warble-800HZ to 1200HZ  
1 second ramp cycle
- **Operating Temp:** -20°C to 60°C
- **Dimensions:** 4.3"Wx4.3"Wx2"D  
(108mmx108mmx56mm)
- **Color:** White

AVAILABLE SPECIAL ORDER ONLY

### TANE SCH 101 • Speaker



**Specifications:**

- **Housing Material:** ABS Plastic
- **Speaker:** Voice coil impedance-8 ohm
- **Input Power Rating:** 15 watts continuous  
20 watts peak
- **Sound Level:** 110db/m
- **Dimensions:** 4.3"x4.3"x2"  
(108mmx108mmx56mm)
- **Color:** White

AVAILABLE SPECIAL ORDER ONLY

### TANE SIR 202 • Self Contained Siren Horn



**Specifications:**

- **Housing Material:** ABS Plastic
- **Speaker Type:** Dual Tone Siren Horn
- **Rated Input Voltage:** 12 VDC
- **Range Voltage:** 6-15VDC
- **Sound Level:** 115db
- **Speaker Type:** Horn
- **Power Rating:** 15 watts
- **Tone Frequency:** Steady-1200HZ  
Warble-800HZ to 1200HZ  
1 second ramp cycle
- **Operating Temp:** -20°C to 60°C
- **Dimensions:** 5.2"Dx5.9"Lx5.2"H  
(132mmx150mmx132mm)
- **Color:** White

AVAILABLE SPECIAL ORDER ONLY

### TANE SPK 202 • Speaker Horn



**Specifications:**

- **Housing Material:** ABS Plastic
- **Speaker:** Voice coil impedance-6 ohm
- **Input Power Rating:** 15 watts max.
- **Sound Level:** 115db
- **Operating Temp:** -20°C to 60°C
- **Dimensions:** 5.2"Dx5.9"Lx5.2"H  
(132mmx150mmx132mm)
- **Color:** White

AVAILABLE SPECIAL ORDER ONLY

### TANE SIR 5FL • Flush Mount Dual Tone Indoor Siren



**Specifications:**

- **Housing Material:** ABS Plastic
- **Speaker Type:** Voice coil impedance-8 ohm
- **Rated Input Voltage:** 12 VDC
- **Range Voltage:** 6-15VDC
- **Sound Level:** 100db
- **Current Draw:** 400mA @12VDC 8 ohm load
- **Tone Frequency:** Steady-1200HZ  
Warble-800HZ to 1200HZ  
1 second ramp cycle
- **Operating Temp:** -20°C to 60°C
- **Dimensions:** 4.3"x4.3"x2"  
(108mmx108mmx56mm)
- **Color:** White

AVAILABLE SPECIAL ORDER ONLY

### TANE SPK 5FL • Flush Mount Speaker



**Specifications:**

- **Housing Material:** ABS Plastic
- **Speaker:** Voice coil impedance-8 ohm
- **Speaker Type:** Cone
- **Input Power Rating:** 15 watts max.
- **Sound Level:** 110db
- **Dimensions:** 6.4"x5.04"x1.61"  
(163mmx127mmx41mm)
- **Color:** White

AVAILABLE SPECIAL ORDER ONLY

### TANE SIR 508 • 30 Watt 5x8 Electronic Siren



**Specifications:**

- **Housing Material:** ABS Plastic
- **Speaker Type:** 30 Watt Dual Tone Siren
- **Rated Input Voltage:** 12 VDC
- **Range Voltage:** 6-15VDC
- **Sound Level:** 120db
- **Current Draw:** 1500mA @12VDC
- **Tone Frequency:** Steady-1200HZ  
Warble-800HZ to 1200HZ  
1 second ramp cycle
- **Operating Temp:** -20°C to 60°C
- **Dimensions:** 5"Hx8"Lx9"H  
(127mmx203mmx229mm)
- **Color:** White

AVAILABLE SPECIAL ORDER ONLY

### TANE SPK 508 • 30 Watt 5x8 Speaker/Horn



**Specifications:**

- **Housing Material:** ABS Plastic
- **Speaker:** Voice coil impedance-8 ohm
- **Speaker Type:** Horn
- **Input Power Rating:** 30 watts max.
- **Sound Level:** 120db
- **Dimensions:** 5"x8"x9"  
(108mmx108mmx56mm)
- **Color:** White

AVAILABLE SPECIAL ORDER ONLY



The Best Guarantee Since 1984 : \$50-1

## TANE ALARM PRODUCTS

906 JERICHO TURNPIKE, NEW HYDE PARK, NY 11040

Tel: 800-852-5050 • 516-328-3351 • Fax: 516-326-9125

www.tanealarm.com • E-MAIL: info@tanealarm.com